

NoTap

NoTap Big for T-pipe (branch) connections



With NoTap Big tools you can make T-pipe (branch) connections in bigger dimensions than with the NoTap series K1. You can use tools on pipes from Cu 54 up to DN 300 and make outlets in dimensions 1.5", 2.0" and 2.5" using three different tools. The tools are available as sets in different combination. The clamps have no return valve. A ball valve of standard type must be added.

Technical specifications

| Dimensions: | Clamp outlet | Pipes |
|-------------|--------------|---|
| | DN40, 1 1/2" | Cu 54, DN50, Cu 70, DN65/Cu 76,1, DN80/Cu 88,9, Cu 159 |
| | DN50, 2" | Cu 70, DN65/Cu 76,1, DN80/Cu 88,9, Cu 100, Cu 108, DN100 |
| | DN65, 2 1/2" | DN80/Cu 88,9, Cu 100, Cu 108, DN100, DN125/Cu 133, Cu 159, DN150, DN200, DN250, DN300 |

Max system pressure: 16 bar (pipe dimensions up to DN125/Cu 133)
10 bar (pipe dimensions from DN150 and larger)

Max temperature: +105°C

Min temperature: - 10°C

Pipe material: All types of metal (copper, stainless steel, galvanised and iron)

Media: Potable water, heating, cooling systems (glycol or salt-water based refrigerants) and compressed air systems. Please contact us regarding other applications.

Tigerholm